MATERIAL SAFETY DATA SHEET

Hyponex®

73201570

Charcoal

Hyponex Corporation 14111 Scottslawn Road Marysville, Ohio 43041 In Case of Emergency call: 1-937-644-0011 (USA) For non-Emergency calls: 1-937-644-0011 (USA)

I. MATERIAL IDENTIFICATION

Product Name:

Hyponex® Charcoal

Analysis:

N/A

Stock Number:

73201570

NFPA Hazard Ratings

0 Least

Health Flammability 1 Slight
2 Moderate

Reactivity

0 0

2

3 High 4 Severe

II. COMPOSITION/INGREDIENTS

No direct hazardous components are known. This product contains 100% charcoal.

All organic materials contain natural inherent bacteria for the breakdown or decomposition of organic matter.

III. FIRST AID PROCEDURES

Eyes:

Flush with water for 15 minutes holding eyelids open. Get medical attention if irritation persists.

Ingestion:

Induce vomiting or perform gastric lavage if large amounts are ingested. Symptomatic and supportive care.

Skin:

Wash thoroughly. If irritation persists, get medical attention.

Inhalation:

Remove to fresh air. Treat symptomatically.

IV. HEALTH HAZARD INFORMATION

Summary of Risks:

May irritate skin and eyes. Slight, causes readily reversible changes which disappear

after end of exposure.

Primary Entry Route(s):

Ingestion.

Acute Effects:

See summary.

Chronic Effects:

None known.

Medical conditions which may be aggravated by contact:

Skin abrasions and sores. Inhalation of dust may

aggravate asthma.

Ingredients Listed as a Carcinogen:

IARC Monographs: No

NTP:

No

OSHA:

No

Page 2 of 2 Product Name: HYPONEX® CHARCOAL (Stock # 73201570)

V. PERSONAL PROTECTION AND PRECAUTIONS

Eve Contact:

Protective eye wear is usually not required for normal use.

Gloves:

Gardening gloves are suggested.

Respiratory:

Reactivity

Stability:

If airborne dust levels are high, a dust mask is recommended to avoid inhalation.

VI. PHYSICAL HAZARD INFORMATION

Fire and Explosion

N/A

Flash Point (Test Method): Flammable Limits (% in Air):

Auto Ignition Temperature:

N/A N/A **Physical Properties**

Appearance:

Black amorphous solid

Melting Point: **Boiling Point:**

3500°C 4200°C

Solubility in H₂0:

Negligible

Specific Gravity:

30 gms. per C.C.

Vapor Pressure:

N/A

Stable

Evaporation Rate:

N/A

Hazardous Polymerization:

Will not occur

Conditions to Avoid:

Open flame and fire.

Hazardous Decomposition Products:

In a fire, oxides of carbon would be expected.

Chemical Incompatibilities:

None known

Unusual Fire, Explosion

May be subject to spontaneous heating, when wet, freshly

and Reactivity Hazards:

calcined or tightly packed.

In Case of Fire:

Use self-contained air supply.

Extinguishing Media:

Water spray

VII. REGULATORY INFORMATION

DOT Classification:

Not classified as hazardous.

VIII. STORAGE AND SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage:

Avoid container breakage, keep away from feed or foodstuffs. Store under dry conditions, away from extreme heat.

Wash after handling. Keep out of reach of children.

In case of spills:

Sweep up spills. Use good housekeeping practices. Avoid contact with skin, eyes, or clothing. Wash after handling.

Waste management/disposal:

Remove to approved landfill.

Revised:

Date Issued:

3/28/97

The information contained herein is, to the best of Scott's knowledge and belief, accurate and reliable as of the date of preparation of this document. However, no warranty or guarantee, express or implied, is made as to the accuracy or reliability, and Scotts shall not be liable for any loss or damage arising out of the use thereof. No authorization is given or implied to use any patented invention without a license. In addition, Scotts shall not be liable for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices or from any hazards inherent in the nature of the product.